FAS-N-LOKT TEETH & HOLDERS - 16R55 SERIES





Elminate the need for Rubr-Lok with this new design which incorporates vulcanized rubber on to the inside surface of the tooth.

16R55 Replacement Series



Part No.	Description	Application	n Installation in P-2070		. Wt. kg.					
			1111 -2070	lbs.	ĸg.					
140019	16R55 Dirt	ordinary digging	yes	1.0	.5					
140018	7R55 Carbide Chisel	abrasive soils	no	12 oz.	.3					
The following teeth are not available in the Fas-N-Lok series.										
You will need to use Rubr-Lok for with these teeth, two 4' coils are included in each box of teeth.										
140513	16R55HF Carbide	high abrasion	yes	1.2	.6					
140509	16R51 Bident	ordinary digging	yes	1.0	.5					
140390	7R55 Chisel	compacted soils	no	12 oz.	.3					



Holders for 16R55 Series Teeth

Part No.	Description	Approx. Wt.	
		lbs. kg.	
155000	B-256	2.5 1.1	
155010	C-355	3.0 1.4	
154990	E-555	2.5 1.1	

Dirt: for use in the most common digging conditions. Thin cross section for best penetration; maintains sharp cutting edge.

Chisel point: easily penetrated compacted soil, sandstone, hardpan, caliche, etc. For use in inside pockets of head.

100th & Holder Dimensional Data								
Description	Side A	Side B	Side C	Standard Qty.	Approx. Wt.			
16R55 Dirt 7R55 Chisel	2" 7/8"	2 1/4" 2 1/4"	11/16" 11/16"	50 50	50 40			

Forged from heat treated alloy steel.

Installs easily and quickly, yet holds securely.