Winter grade air tool lubricant that prevents air line, air tool and in-line lubricator freeze-up..





- can be poured directly into tool or used with air line lubricators
- performance is good to -45°F

Size	Part #	Opt Qty		
1 pint	DATL016W	12		
1 gallon	DATL128W	4		


E Air

Bar Manifolds

The bar manifold can be mounted on a wall or work bench, safely distributing four hose lines to a work area.

- maximum working pressure is 300 PSI at ambient temperature (70°F)
- brass hex head plugs sold on page 303





Aluminu	um	Λ	R	_			г		11	
Part #	Price/E	A	В		D	E	Г	G		J
AMF32	\$71.95	1/4"	7-5/8"	7/8"	1-1/4"	1-7/8"	3-3/4"	1 ¹¹	3/8"	.20"
AMF42	71.95	1/4"	7-5/8"	1-1/8"	1-1/2"	1-7/8"	3-3/4"	1"	1/2"	.20"
AMF43	71.95	3/8"	8"	1-1/8"	1-1/2"	2"	4"	1"	1/2"	.20"

3 in 1 Manifolds

Applications:

 supplies 3 air operated tools from a single hose, permits use of air by more than one mechanic



- · mount to pipe at workbench or overhead
- different tools in the shop use different styles of couplers, mount 3 different style couplers on one manifold

NPT Inlet	NPT Outlet	Aluminum	
(1)	(3)	Part #	
1/4"	1/4"	D3404	-5
3/8"	1/4"	D3406	
1/2"	1/4"	D3408	

2 in 1 Manifolds

Applications:

 supplies 2 air operated tools from a single hose, permits use of air by more than one mechanic



- · mount to pipe at workbench or overhead
- different tools in the shop use different styles of couplers, mount 2 different style couplers on one manifold

