

## Grades 80 & 100 Alloy Chain (KLB)

Gunnebo Lifting has been manufacturing chain products since the middle 1800's. We manufacture a wide size range of both Grades 80 & 100 alloy chain for overhead lifting and chain for commercial fishing and aquaculture. Gunnebo Lifting chain is thru-hardened for maximum resistance to distortion, gouging, and wear, yet remains ductile for excellent elongation. This is an ideal combination for Grades 80 & 100 alloy steel chain sling fabrication.

Every link of Gunnebo Lifting's alloy steel chain is proof loaded to 2 1/2 times the minimum breaking strength. While normally packaged in drums, boxed quantities are also available. Gunnebo Lifting alloy steel chain is also an excellent cargo-control or tie-down item and is frequently used on heavy transfer trailers. Gunnebo Lifting's steel Commercial Fishing chain is offered in mid-link and long-link and is well suited for most all fishing applications.

- Each link calibrated & pull tested to 2 1/2 times working load limit
- Minimum elongation of 20%
- Fully hardened & tempered alloy steel
- Distinctive black finish
- Links embossed with grade and traceability code



MODEL	CHAIN SIZE	GRADE	WORKING LOAD LIMIT	DIMENSIONS (INCHES)			WEIGHT 100 FT
	(INCHES)		* (Lbs) at 90°	D	E	H	lbs
KLB-7-10	9/32	100	4,300	0.28	0.83	0.41	77
KLB-8-10	5/16	100	5,700	0.32	0.94	0.45	97
KLB-10-10	3/8	100	8,800	0.40	1.18	0.57	151
KLB-13-10	1/2	100	15,000	0.52	1.54	0.72	253
KLB-16-10	5/8	100	22,600	0.65	1.89	0.91	394
KLB-20-10	3/4	100	35,300	0.81	2.36	1.12	630
KLB-22-8	7/8	80	34,200	0.87	2.60	1.20	715
KLB-26-8	1	80	47,700	1.02	3.07	1.38	961
KLB-32-8	1-1/4	80	72,300	1.26	3.78	1.69	1545

\* Design Factor 4:1 Proof tested and certified

