

## HALF LINK WITH PIN/LOCK WASHER - SKT

| Stock No. | Model       | Chain Size In. | Grade | Working Load Limit *(Lbs) | L   | Dimensions (Inches) |      | E    | Weight Each (Lbs.) |
|-----------|-------------|----------------|-------|---------------------------|-----|---------------------|------|------|--------------------|
|           |             |                |       |                           |     | B                   | G    |      |                    |
| 545931    | SKT-7/8-8   | 9/32"          | 80    | 3,500                     | 1.1 | 0.71                | 0.35 | 0.87 | 0.22               |
| 545931    | SKT-7/8-8   | 5/16"          | 80    | 4,500                     | 1.1 | 0.71                | 0.35 | 0.87 | 0.22               |
| 545932    | SKT-10-8    | 3/8"           | 80    | 7,100                     | 1.3 | 1.0                 | 0.5  | 1.0  | 0.44               |
| 545933    | SKT-13-8    | 1/2"           | 80    | 12,000                    | 1.7 | 1.1                 | 0.6  | 1.3  | 0.88               |
| 545934    | SKT-16-8    | 5/8"           | 80    | 18,100                    | 2.0 | 1.4                 | 0.7  | 1.6  | 1.5                |
| 545935    | SKT-18/20-8 | 3/4"           | 80    | 28,300                    | 2.5 | 1.7                 | 0.9  | 1.9  | 2.4                |
| 545226    | SKT-22-8    | 7/8"           | 80    | 34,200                    | 3.0 | 2.0                 | 0.9  | 2.4  | 3.7                |
| 545227    | SKT-26-8    | 1"             | 80    | 47,700                    | 3.1 | 2.3                 | 1.1  | 2.4  | 5.7                |
| 545228    | SKT-32-8    | 1 1/4"         | 80    | 72,300                    | 3.9 | 2.8                 | 1.4  | 3.1  | 10.8               |

\* Design Factor 4:1 Proof tested and certified.

Note: G80 SKT for use with G80 SKLI, SKO, SKG, SKS, SKR, SKH, SKN & G-Link only

SKT assembly includes connector, pin, and locking spring

