

# Cord Reels & Drop-Lites

Convenience and added mobility are just two of the benefits Klein cord reels and drop-lites offer. Heavy-duty construction and design make them perfect for any job while keeping work areas clutter-free.

FOR PROFESSIONALS... SINCE 1857®



Cord Reels & Drop-Lites



# Cordomatic® Cord Reels & Drop-Lites

## Drop-Lite Reels

- Cord pulls out, locks and retracts automatically with a quick tug-and-release motion.
- Ceiling-mount reels allow 360° rotation; wall-mount 180° side-to-side rotation.
- Rugged steel case.
- Cord is 3-conductor (grounded) type.
- Reel with grounded convenience outlet in the handle plus push-button switch.
- The 3-conductor grounded cord has molded plug and swing-open metal lamp guard with one-piece hanger hook.
- Circuit breaker resets (Cat. Nos. 900G and 950G).

Cat. No.	Cord Type	UL Rated	Cord Length	Diameter of Reel	Weight (lbs.)
950G	18/3 SVT cord	7A/125V	50' (15 m)	9-1/2" (241 mm)	7.55
900G	18/3 SJT cord	7A/125V	30' (9 m)	9-1/2" (241 mm)	7.01
<b>Heavy-Duty Service</b>					
S900G	SJT 16/3 cord	10A/125V	30' (9 m)	9-1/2" (241 mm)	7.17



950G

## Power-Outlet Reel

- Cord pulls out, locks and retracts automatically with a quick tug-and-release motion.
- Ceiling-mount reels allow 360° rotation; wall-mount 180° side-to-side rotation.
- Rugged steel case.
- Cord is 3-conductor (grounded) type.
- 50-ft. reel with 3-conductor grounded cord with receptacle.
- Circuit breaker resets.

Cat. No.	Cord Type	UL Rated	Cord Length	Diameter of Reel	Weight (lbs.)
900P	18/3 SVT cord	7A/125V	50' (15 m)	9-1/2" (241 mm)	6.97



900P

## Fluorescent Drop-Lite Reel

- Cord pulls out, locks and retracts automatically with a quick tug-and-release motion.
- Ceiling-mount reels allow 360° rotation; wall-mount 180° side-to-side rotation.
- Rugged steel case.
- Cord is 3-conductor (grounded) type.
- 50-ft. grounded fluorescent reel provides cool, energy-efficient light.
- Shatter-resistant shield with a no-glare reflector.
- Instant starter switch in handle.
- Convenient hanging hook.
- Grounded plug-in ballast with grounded safety cord.
- 15-watt fluorescent bulb included.

Cat. No.	Cord Type	UL Rated	Cord Length	Diameter of Reel	Weight (lbs.)
900FL	18/2 SVT cord	15W/117V	50' (15 m)	9-1/2" (241 mm)	7.53



900FL

Note: It is important that users of this product read, understand, and follow all instructions, cautions, and warnings attached to and/or packed with the product.

All dimensions are in inches and (millimeters) unless otherwise specified.



## Retractable Fluorescent Lite

- Cord pulls out, locks and retracts automatically with a quick tug-and-release motion.
- Ceiling-mount reels allow 360° rotation; wall-mount 180° side-to-side rotation.
- Rugged steel case.
- Cord is 3-conductor (grounded) type.
- Compact, energy-efficient, dual-bulb fluorescent light with a non-glare reflector for high light levels in small areas.
- Shatter-resistant shield.
- Instant starter switch in handle.
- Convenient hanging hook.
- Cord ball-stop.
- Grounded plug-in ballast and grounded safety cord.
- Furnished with 13-watt dual fluorescent bulb.

Cat. No.	Cord Type	UL Rated	Cord Length	Diameter of Reel	Weight (lbs.)
35325	18/2 cord	117V	40' (12 m)	9-1/2" (241 mm)	8.03



35325

## "500" Series Handy-Lite Reels

- Reels can be easily mounted on wall or ceiling and include a locking mechanism.
- Swivel-hook allows the reel to rotate when hung on ceiling.
- Cord pulls out, locks, and retracts automatically with a quick tug-and-release motion.
- Bulbs not included.

Cat. No.	Description	Cord Type	UL Rated	Cord Length	Diameter of Reel	Weight (lbs.)
500	push-button switch in handle and plastic guard with one-piece hanger hook, but no convenience outlet	18/2 SVT 2-conductor cord	6A-125V	20' (7.5 m)	6-1/2" (165 mm)	3.15
500G	grounded outlet and push-button switch in handle, plus steel lamp guard	18/3 SVT 3-conductor cord	7A-125V	20' (7.5 m)	6-1/2" (165 mm)	3.19
500P	power outlet reel with one-outlet receptacles in place of hand lamp for plugging in tools	18/3 SVT 3-conductor cord	7A-125V	20' (7.5 m)	6-1/2" (165 mm)	3.12



500

## Drop-Lite with 3-Conductor Cord

- Heavy-duty construction.
- Steel swing-open guard with hanger hook.
- 3-conductor cord with molded plug cap.
- Push-button switch.
- Convenience outlet.
- Comfortable grip.
- Bulb not included.

Cat. No.	Cord Type	UL Rated	Cord Length	Weight (lbs.)
125DCG	18/3 SJT	10A-125V	25' (7.5 m)	1.79
150DCG	18/3 SJT	10A-125V	50' (15 m)	3.18
225DCG	16/3 SJT	13A-125V	25' (7.5 m)	2.37
250DCG	16/3 SJT	13A-125V	50' (15 m)	3.95



125DCG

Note: It is important that users of this product read, understand, and follow all instructions, cautions, and warnings attached to and/or packed with the product.

All dimensions are in inches and (millimeters) unless otherwise specified.



## Fluorescent Drop-Lite

- Provides cool, energy-efficient illumination.
- Shatter-resistant shield with a no-glare reflector.
- Instant-starter switch in handle.
- Convenient hanging hook.
- Grounded plug-in ballast.
- 15-watt fluorescent bulb.



Cat. No.	Cord Type	Cord Length	Weight (lbs.)
825FL	18/2 SJT	25' (7.5 m)	2.74



825FL

## Deluxe Handle Assembly

- Has swing-open guard, comfortable, impact-resistant handle.
- Bulb not included.
- Grounding-type steel guard, push-button switch, and convenience outlet.

Cat. No.	Weight (lbs.)
400HAG	.48



400HAG

