

Hammers, Chisels & Punches

Klein hammers, chisels, and punches are designed and created to strike through jobsite challenges. Engineered with the professional in mind, each hammer, chisel, and punch is job-matched to fit the task at hand.

F O R P R O F E S S I O N A L S . . . S I N C E 1 8 5 7 .



Hammers, Chisels
& Punches



Hammers

Electrician's Straight-Claw Hammer

- Durable plastic-alloy jacketing helps to protect neck from fraying and splintering if incorrectly struck or overstruck.
- High-strength fiberglass shaft absorbs shock and keeps head tight.
- Comfortable, perforated neoprene grip bonded to handle.
- Correctly balanced and designed specifically for use in electrical work.
- Extra-long neck, and narrow striking face are ideal for reaching into outlet boxes and other tight areas.



807-18

Cat. No.	Head Weight	Overall Length	Weight (lbs.)
807-18	18 oz. (510 g)	15" (381 mm)	1.85

Straight-Claw Hammers – Heavy-Duty

- Durable plastic-alloy jacketing helps to protect neck from fraying and splintering if incorrectly struck or overstruck.
- High-strength fiberglass shaft absorbs shock and keeps head tight.
- Comfortable, perforated neoprene grip bonded to handle.
- Straight-claw design for easy nail pulling in tight quarters.



808-16

Cat. No.	Head Weight	Overall Length	Weight (lbs.)
808-16	16 oz. (454 g)	13" (330 mm)	1.85
808-20	20 oz. (567 g)	14" (356 mm)	2.00

Curved-Claw Hammers – Heavy-Duty

- Durable plastic-alloy jacketing helps to protect neck from fraying and splintering if incorrectly struck or overstruck.
- High-strength fiberglass shaft absorbs shock and keeps head tight.
- Comfortable, perforated neoprene grip bonded to handle.
- Curved claw gives maximum nail-pulling leverage.



818-16

Cat. No.	Head Weight	Overall Length	Weight (lbs.)
818-16	16 oz. (454 g)	13" (330 mm)	1.85
818-20	20 oz. (567 g)	14" (356 mm)	2.00

Ball-Peen Hammers

- High-carbon steel head is forged and hardened.
- Crowned face with uniform bevel.
- Smoothly rounded peen.
- Straight-grain hickory handle is stained and lacquered.



803-12

Cat. No.	Head Weight	Overall Length	Weight (lbs.)
803-8	8 oz. (227 g)	11-1/2" (292 mm)	.75
803-12	12 oz. (340 g)	12-1/2" (318 mm)	1.10
803-16	16 oz. (454 g)	13-1/2" (343 mm)	1.40
803-24	24 oz. (680 g)	15" (381 mm)	1.90
803-32	32 oz. (907 g)	15" (381 mm)	2.50

Lineman's Straight-Claw Hammer

- Heavy-duty, double-duty hammer drives lags and pulls big nails.
- Special high-carbon steel head with solid, octagon-shaped driving end and thick, strong claw.
- Blue painted finish.
- Straight-grain hickory handle, lacquered.



832-32

Cat. No.	Head Weight	Overall Length	Weight (lbs.)
832-32	32 oz. (907 g)	15" (381 mm)	2.50

All dimensions are in inches and (millimeters) unless otherwise specified.

⚠ WARNING: Always wear approved eye protection.



Lineman's Double-Face Hammer

- Designed for pole-line work.
- Rugged and well-balanced, with the weight to drive lag bolts.
- Forged, tempered-steel head is only 3-3/4" (95 mm) long for use in tight areas.
- Identical faces with 1-3/4" (44 mm) round-crown driving surface and beveled edges.



809-36

Cat. No.	Head Weight	Overall Length	Weight (lbs.)
809-36	36 oz. (1021 g)	14" (356 mm)	2.50

Hand-Drilling Hammer

- Extra-heavy, forged steel head, hardened and tempered.
- Short handle for working in close quarters.
- Select hickory handle, triple-wedged and lacquered.
- Special handle treatment removes handle moisture and replaces it with oil to help eliminate the effects of extreme temperatures.



823-48

Cat. No.	Head Weight	Overall Length	Weight (lbs.)
823-48	48 oz. (1361 g)	10" (254 mm)	3.25

Chisels

Cold Chisels

- Heat-treated, high-carbon steel for necessary hardness and durability.
- Cuts, shapes, and removes metal.
- Corrosion resistant black finish.



66142

Cat. No.	Blade Width	Overall Length	Weight (lbs.)
66140	3/8" (10 mm)	5" (127 mm)	.10
66142	1/2" (13 mm)	6" (152 mm)	.20
66143	5/8" (16 mm)	6-1/2" (165 mm)	.35
66144	3/4" (19 mm)	7-1/2" (191 mm)	.60
66145	7/8" (22 mm)	8" (203 mm)	.85
66146	1" (25 mm)	8-1/2" (216 mm)	1.31

Cold Chisels – Long-Length



66177

- Heat-treated, high-carbon steel for necessary hardness and durability.
- Cuts, shapes, and removes metal.
- Correctly ground edge and long length work better in hard-to-reach areas.
- Corrosion resistant black finish.

Cat. No.	Blade Width	Overall Length	Weight (lbs.)
66174	1/2" (13 mm)	12" (305 mm)	.40
66177	3/4" (19 mm)	12" (305 mm)	1.05
66183	1" (25 mm)	12" (305 mm)	2.05

All dimensions are in inches and (millimeters) unless otherwise specified.

⚠ WARNING: Always wear approved eye protection.



Chisels

Electrician's Chisel

- One-piece forged handle and blade of strong alloy steel.
- Corrosion resistant black finish extends to the polished blade edge.



Cat. No.	Blade Width	Overall Length	Weight (lbs.)
66100	2-3/4" (70 mm)	8" (203 mm)	1.10

Punches

Drift Punches

- High-carbon steel for durability.
- Rugged design for impact strength.
- Strong, heat-treated points are smooth and correctly tapered.
- Corrosion resistant black finish.



Cat. No.	Point	Taper	Overall Length	Weight (lbs.)
66340	1/8" (3 mm)	4-1/4" (108 mm)	8" (203 mm)	.20
66342	3/16" (5 mm)	5" (127 mm)	9" (229 mm)	.35
66343	1/4" (6 mm)	5-1/2" (140 mm)	11" (279 mm)	.75
66344	5/16" (8 mm)	5-1/2" (140 mm)	11" (279 mm)	.75

Center Punches

- High-carbon steel for durability.
- Rugged design for impact strength.
- Smooth-ground points heat-treated to stay sharp and true longer.
- Corrosion resistant black finish.



Cat. No.	Shank Diameter	Overall Length	Weight (lbs.)
66310	1/4" (6 mm)	4 1/4" (108 mm)	.05
66311	5/16" (8 mm)	4 1/2" (114 mm)	.10
66312	3/8" (10 mm)	5" (127 mm)	.10
66313	1/2" (13 mm)	6" (152 mm)	.25

Pin Punches

- High-carbon steel for durability.
- Precision-ground shank.
- Heat-treated for added strength and hardness at working end.
- Corrosion resistant black finish.



Cat. No.	Point Diameter	Overall Length	Weight (lbs.)
66320	1/16" (1.5 mm)	4-1/4" (108 mm)	.05
66321	3/32" (2 mm)	4-3/4" (121 mm)	.10
66322	1/8" (3 mm)	5" (127 mm)	.10
66323	5/32" (4 mm)	5-1/4" (133 mm)	.10
66324	3/16" (5 mm)	5-1/2" (140 mm)	.10
66325	1/4" (6 mm)	7" (178 mm)	.20

All dimensions are in inches and (millimeters) unless otherwise specified.

⚠ WARNING: Always wear approved eye protection.

