




### Features


- Parker HA Series couplings are interchangeable with ARO's 210 series couplings. See Table of Contents.
- Push to Connect design for easy one hand operation.
- HA Series couplings utilize a tubular valve for maximum flow and a built-in sleeve guard to minimize accidental disconnect.
- The HA Series is only available in 1/4" body size.
- HA Series couplings have all brass bodies.
- Standard seal material is Nitrile. See the Coupling Selection and Ordering Information Guide at the beginning of Section A and the Fluid Compatibility Chart at the end of this catalog for optional materials.
- Other port options available – contact the division.
- Formerly the 50A Series.

### Couplers

#### Female Pipe Thread




#### Male Pipe Thread



### Specifications


Body Size (in.Z)	1/4
Rated Pressure (psi)	300
Temperature Range (Std. seals)	-40° to +250° F
Locking Device	4 balls
Vacuum Service	<b>Not Recommended</b>

### Performance



### How To Order

#### HA - 251 - 4FP - \*



Body Size (in.Z)	NEW Part No. Brass	OLD Part No. Brass	Thread Size NPSF	Dimensions (in.Z)			Largest Diameter P/Piece	Wt. (LBZ)
				Overall Length	Hex Size	Overall Length		
1/4	HA-251-4FP	C50A02-4-4	1/4-18	2.11	0.81	1.01	0.26	
1/4	HA-251-6FP	C50A02-4-6	3/8-18	2.14	0.81	1.01	0.27	

Body Size (in.Z)	NEW Part No. Brass	OLD Part No. Brass	Thread Size NPSF	Dimensions (in.Z)			Largest Diameter P/Piece	Wt. (LBZ)
				Overall Length	Hex Size	Overall Length		
1/4	HA-251-4MP	C50A01-4-4	1/4-18	2.26	0.81	1.01	0.24	
1/4	HA-251-6MP	C50A01-4-6	1/4-18	2.26	0.81	1.01	0.24	

\* See page A-15 for Nipples